

CASE 13 A

(SEE NOTE 7)

CASE 13 B

(SEE NOTE 7)

DETAIL

## NOTES

- 1. See Contract Plans for guardrail connection to bridge rail and concrete barrier.
- 2. The slope from the edge of the shoulder into the face of the guardrail should not be steeper than 10:1.
- 3. Fewer CRT posts are required for smaller radii; include CRT Post at Point B. Attach guardrail to post with a 5/16" x 9" long bolt, a 3/8" I.D. x 7 1/2" snug fitting inser and a 1 1/2" washer with nut on back of post.
- 4. For terminal type and details, see Contract and applicable Standard Plan(s).
- 5. Radius dimensions shall be etched into plate replacing the letters "HH", shown on the GUARDRAIL RADIUS IDENTIFICATION PLATE DETAIL. Digits shall be 1 1/2" minimum height and 3/4" maximum width. Plate shall be galvanized after etching.
- The guardrail radius Identification Plate shall be mounted on the back side of the rail element using the lowest splice bolt nearest the PC of the guardrail radius (See View A).
- 7. The first letter of the Case Designation indicates the end treatment on the side road. The second letter indicates the end treatment on the main road. For example, a Type 5 Anchor on the side road with a bridge connection on the main road would be Case 13 AC, the combination shown.
- 8. For CRT post details, see Standard Plan C-1b.



GUARDRAIL PLACEMENT WEAK POST INTERSECTION DESIGN (35' MAX. RADIUS) STANDARD PLAN C-2g

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE.
THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE
AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A COPY MAY BE OBTAINED
UPON REQUEST.

7/O1 CORRECTED NOTES; ADDED "VIEW A" MAS

REVISION

DATE

APPROVED FOR PUBLICATION

Clifford E. Mansfield 07-27-01

Clifford E. Mansfield
STATE DESIGN ENGINEER

Washington State Department of Transportation